

Product Comparison Table

LED Beacon



	C12	C24	FD24
ITEM	080405/080402	080106/080102	080601(AT / AM / AF / AS)
LED Power	12PCS 3W LED	24PCS 3W LED	24PCS 1W LED
LED Lifespan	100,000H	100,000H	100,000H
Flash settings	1-4HZ	1-4HZ	1-4HZ
LENS	Reflex	Reflex	Reflex
Voltage	DC 10-30V	DC 10-30V	DC 10-30V
Max Power	19W	37W	30W
Colour Available	Amber,Blue	Amber,Blue	Amber
Ambient temperature	-20--+65 °C	-20--+65 °C	-30--+70 °C
Waterproof	IP67	IP67	IP68
Flash patterns	22	22	8(including rotating)
Housing Materials		Plastic	
Mounting	080405:Sucker with Magnet Mount; 080402:Permanent Mount	080106:Sucker with Magnet Mount; 080102:Permanent Mount	Four kinds of installation(3 point / Magnetic / Flexi DIN / Single Point)
Meet and Exceeds	ECE R65 TA1 TB1, ECE R10,SAE	ECE R65 TB2 TA2,ECE R10 ,SAE	ECE R65 TA1
Wire	080405:6m long spring line with A13-E163 cigarette lighter. 080402:50cm long 4-core wire	080106:6m long spring line with A13-E163 cigarette lighter. 080102:50cm long 4-core wire	AT / AF / AS:35cm long 4-core wire AM:6m long spring line with A13-E163 cigarette lighter
Warranty	2 years	2 years	2 years
Listing Date	2013	2013	2014
Max Speed with magnet mount	140 KM/H SPEED TEST	140 KM/H SPEED TEST	140 KM/H SPEED TEST