

Product Comparison Table

LED Warning Light Bar



C4-SERIES

PIONEER

	C4-2	C4-4	C4-8	PT4-2	PT4-4	PT4-6	PT4-8
ITEM	040101	040102	040103	040301	040302	040303	040304
LED Power	8 PCS 3W LED	16 PCS 3W LED	32PCS 3W LED	8 PCS 3W LED	16PCS 3W LED	24PCS 3W LED	32PCS 3W LED
LED Lifespan	100000H	100000H	100000H	100000H	100000H	100000H	100000H
Flash settings	1-4HZ	1-4HZ	1-4HZ	1-4HZ	1-4HZ	1-4HZ	1-4HZ
LENS	Reflex	Reflex	Reflex	TIR	TIR	TIR	TIR
Voltage	DC 10-30V	DC 10-30V	DC 10-30V	DC 10-30V	DC 10-30V	DC 10-30V	DC 10-30V
Max Power	19W	32W	72W	18W	29W	50W	71W
Colour Available	amber, red, blue, white and combination color						
Ambient temperature	-20--+65 °C						
Waterproof	IP67	IP67	IP67	IP65	IP65	IP65	IP65
Product Dimension	9.0 "Long x 2.2" Wide x 1.0"High	19.0 "Long x 2.2" Wide x 1.0"High	36.0 "Long x 2.2" Wide x 1.0"High	11.0 "Long x 2.2" Wide x 1.8"High	22 "Long x 2.2" Wide x 1.8"High	33 "Long x 2.2" Wide x 1.8"High	44.0 "Long x 2.2" Wide x 1.8"High
Flash patterns	19	26		19		30	
Housing Materials	Aluminum alloy Housing						
Mounting	T-Shaped Screws or Bracker						
Meet and Exceeds	ECE R65 XB1 XA1,ECE R10, SAE			ECE R65 XA1,ECE R10, SAE			
Wire	4 core cable	4 core cable	8 core cable	4 core cable	4 core cable	8 core cable	8 core cable
Warranty	2 years						
Listing Date	2012						